

LG 49SE3D B 49" Class SE3D Series LED display energy efficiency class A



Description

Product Description	LG 49SE3D-B SE3D Series - 49" LED display
Product Type	LED-backlit LCD flat panel display
Diagonal Class	49"
Commercial Use	Yes - digital signage
Colour	Black
Resolution	1920 x 1080
Display Format	1080p (Full HD)
Video Interface	HDMI
HDMI Ports Qty	2 ports
Connectivity	Wi-Fi (optional), LAN
PC Interface	DVI, VGA (HD-15)
Technology	IPS
LCD Backlight Technology	LED backlight - edge-lit
Image Aspect Ratio	16:9
TV Tuner	No tuner
Commercial Features	SNMP support, detachable logo, Local Time Auto Setting, Contents Scheduling, SuperSign-c compatible, SuperSign-w compatible
USB	Yes
Remote Control	Standard remote
Voltage	AC 120/230 V (50/60 Hz)
Power Consumption Operational	65 Watt
Dimensions (WxDxH) - without stand and speakers	110.22 cm x 3.86 cm x 63.85 cm
Weight	14.1 kg
Environmental Standards	ENERGY STAR Qualified

Technical description

General

Product Type	LED-backlit LCD flat panel display
Power Consumption Operational	65 Watt
Diagonal Class	49"

Commercial Use	Yes - digital signage
Series	SE3D Series
TV Tuner	No tuner
TV Tuner Presence	No
Video Interface	HDMI
HDMI Ports Qty	2 ports
PC Interface	DVI, VGA (HD-15)
Modes	Portrait mode, landscape mode
Dimensions	Without stand and speakers
Width	110.22 cm
Depth	3.86 cm
Height	63.85 cm
Weight	14.1 kg
Enclosure Colour	Black

Display

LCD Display Technology	IPS
Resolution	1920 x 1080
Display Format	1080p (Full HD)
Image Aspect Ratio	16:9
LCD Backlight Technology	LED backlight - edge-lit
Coating	Anti-glare, 3H Hard, conformal
Image Contrast Ratio	1100:1
Dynamic Contrast Ratio	500000:1
Brightness	350 cd/m ²
Viewing Angle	178 degrees
Viewing Angle (Vertical)	178 degrees
Response Time	10.1 ms
Commercial Features	SNMP support, detachable logo, Local Time Auto Setting, Contents Scheduling, SuperSign-c compatible, SuperSign-w compatible
Operation Hours / Days	18 / 7
Features	Image Sticking Minimization (ISM), Front Polarizer

Stands & Mounts

Stand	Optional
Flat Panel Mount Interface	300 x 300 mm

Media Player

USB Port	Yes
USB Ports Qty	1

Remote Control

Type	Standard remote
------	-----------------

Network & Internet Multimedia

Connectivity	Wi-Fi (optional), LAN
--------------	-----------------------

Connections

Connector Type	Serial input Serial output 2 x HDMI input Audio line-out Infrared input DVI-D input VGA input Network Audio line-in USB 2.0
----------------	---

Miscellaneous

Included Accessories	IR receiver, 2 batteries
Cables Included	VGA cable Serial adapter
Compliant Standards	FCC Class A certified, UL, TUV, cUL, CB, EMC, KCC, KC

Environmental Standards

ENERGY STAR Certified	Yes
ENERGY STAR Version	7.0

Power

Power Device	Power supply
Nominal Voltage	AC 120/230 V (50/60 Hz)
Features	WOL (Wake on LAN)

Dimensions & Weight Details

Dimensions & Weight Details	Panel without stand and without speakers - 110.22 cm x 3.86 cm x 63.85 cm x 14.1 kg Panel with stand and speakers - 110.22 cm x 21.96 cm x 69.68 cm x 17.9 kg Panel with stand - 17.4 kg
-----------------------------	--

Dimensions & Weight (Shipping)

Width (Shipping)	119.7 cm
Depth (Shipping)	16.6 cm
Height (Shipping)	76 cm
Weight (Shipping)	17.2 kg

Environmental Parameters

Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 80%

We take no accountability nor guarantee that all information contained on these pages is current and complete.